

Technical data		
Name		350-6
1 Use		Various
2 Fitting		Double axle
3 Max load	Kg	150-200
4 Type		Brushed / Bless
5 Outer diameter	mm	280-320
6 Power	W	300-400
7 RPM		150
8 Max speed	km/h	10
8 Tire size		3.50-6
10 Voltage	V	24-36
11 Weight	Kg	
12 Wheel type		pneumatic
13 Gearbox		No
14 Max torque	Nm	20
15 Freewheel		yes
16 Brake		No
17 Gearbox		No



**E4037A & B**

<b>E4037A</b>	T (Nm)	N (RPM)	Pout (W)	Voltage	I (A)	Pin (W)	Eta (%)
Pin-max	13,24	71,9	99,69	35,99	6,5	233,91	42,6
N-max	0,08	156,8	1,31	35,97	0,26	9,35	14
Pout-max	12,2	79,4	101,44	35,99	5,98	215,22	47,1
V-max	1,93	124,4	64,23	35,99	2,53	91,05	70,5
I-max	13,24	71,9	99,69	35,99	6,5	233,04	42,6
Pin-max	13,24	71,9	99,69	35,99	6,5	233,04	42,6
Eta-max	2,55	140	37,39	35,97	1,39	50	74,8

<b>E4037B</b>	T (Nm)	N (RPM)	Pout (W)	Voltage	I (A)	Pin (W)	Eta (%)
Pin-max	20,05	91,8	192,75	36,13	10,87	392,73	49,1
N-max	0,06	169,9	1,07	36,11	0,67	24,19	4,4
Pout-max	20,05	91,8	192,75	36,13	10,87	392,73	49,1
V-max	18,17	98	189,55	36,13	9,99	360,91	52,5
I-max	20,05	91,8	192,75	36,13	10,87	392,73	49,1
Pin-max	20,05	91,8	192,75	36,13	10,87	392,73	19,1
Eta-max	6,16	144	97,42	36,11	3,88	140,11	69,5

### Application


**Address**

Nysättersvägen 11, S-741 42 Knivsta Sweden

**Telephone**

+46 (0) 18 341701

[info@electro-mobile.se](mailto:info@electro-mobile.se)

[www.electro-mobile.se](http://www.electro-mobile.se)